



# WISEASY N5

## Non EMV Android Terminal



### More Than Smart

Android OS  
Exquisite & compact ID design  
Powerful battery  
Excellent user experience



### Multiple Application Scenarios

Online top-up  
Logistics scanning  
Tickets printing  
Inventory management



### Diverse Payment Options

Online payment  
Alipay, Wechat Pay  
NFC Card payment  
Digital wallet



**N5 FP**  
(Optional)

- NFC, Bluetooth, Sound wave sensor, high speed thermal printer, integrated design.
- Operated under high/low temperature, in high moisty environment, 1.2m fall protection.
- Support WIFI, 3G, 4G, build powerful network.
- New business operation system, based on Android intelligent operation system and network security architecture design, humanized interaction experience.
- Powerful 5200mAh battery supports 120-hour endurance for smooth working.

**Beijing Wiseasy Technology Co.,Ltd.**

ADD: 7th Floor, Block B, Wangxin Mansion, No.28 Xiaoyun Road, Chaoyang District, 100027, Beijing, China.  
EMAIL: mk@wiseasy.com WEB: www.wiseasy.com

Follow us on:



## Technical Specifications



### Operating System

Android 8.1 WiseOS



### CPU

Quad-core



### Memory

1GB DDR3, 8GB Flash  
Optional: 2GB+16GB



### Display

5.0 inch, Resolution:1280\*720  
High Sensitivity Capacitive  
Touch Screen



### Camera

Front Camera: 0.3 Mega,  
Rear Camera: 0.3 Mega FF,  
Optional: 5.0 Mega AF



### Network

2G/3G/4G



### WiFi

Supports 2.4G, b/g/n



### Bluetooth

BT 4.0+BLE



### GPS

GPS/A- GPS, GLONASS,  
BEIDOU



### NFC

ISO/IEC 14443 Type A&B,  
Felica, Mifare



### Printer

Thermal Printer, Paper:  
58\*40mm



### PSAM

1 PSAM Slot, ISO/IEC 7816



### Memory Extension

Micro SD/TF, 64GB



### USB Port

Micro USB, OTG Supported



### SIM Card Slot

1 Slot, Micro SIM Card,  
15\*12mm



### Audio

1 Speaker



### Auxiliary Lamp

Support Flash, White Light  
Compensation



### Battery

5200mAh



### Power

Input: 100-240V, 50/60Hz  
0.35A  
Output: 5v/2000mA



### Dimensions

194\*77.5\*62 mm



### Weight

450g



### Accessories

Adaptor, USB Cable  
(Optional:Charging Cradle)



### Temperature

Storage temperature: -35°C to 70°C  
Operating temperature: -10°C to 55°C  
Humidity: ≤95%

## Certifications

GSMA / EU CE / Japan MIC&JETA / China CCC / SRC / CTA / FCC / Google GMS