

WISEASY T1

Android EMV Tablet



Diverse Payments



Full Screen Touch Tablet with Magnetic Stand



Commercial Security Operating System



IC/Magnetic Card Reading & Writing



Multiple Interfaces for Peripheral Devices




External Printer



Biometric Features Module (Optional)



- Android 10.1 security operating system, Qualcomm Octa-core processor, running speed is greatly improved.
- Fully compatible with encrypted magnetic stripe card, financial IC card, NFC, BLE, sound wave and other payment technology.
- Full screen tablet touch experience, magnetic suction supports matching use, supports desktop + handheld multi-scene applications.
- Financial level technical security and protection threshold, anti-disassembly, anti-attack, anti-spy protection hardware and structural physical security design.
- Highly integrated industrial design, reserved with multiple USB interfaces, network ports and other interfaces on the base, can be connected to keyboard, printer and other peripherals.



Magnetic Dock Stand



Cashier Box1



Printer M58

Technical Specifications



Operating System
Android 10.1, WiseOS



CPU
Qualcomm Octa-Core
1.8GHz



Memory
2GB+16GB Standard
Optional: 4GB+64GB



Display
11.6 inches,
resolution: 1920*1080
5 points touch screen



Camera
Front camera: 5Mega
Rear camera: 8Mega,
Supports auto focus & flashlight



Network
2G/3G/4G



WIFI
2.4G/5G, 802.11 a/b/g/n/AC



Bluetooth
BT 4.2+BLE



GPS
GPS/AGPS/GLONASS/
Beidou



NFC
13.56MHz, Support EMV2.6b
standard ISO/IEC 14443,
ISO18092, Type A&B, Felica,
Mifare



IC Card Reader
1. ISO7816
2. PBOC3.0 L1/L2



Magnetic Card Reader
ISO7810/7811, Support
three-track two-way manual
swinging



Printer
Bluetooth and USB Printer



USB Port
Type C USB2.0, High Speed,
OTG.



Card Slot
1 * Micro SIM + 1 * Micro
PSAM or 2 * SIM,
Supports DSDS (SAM slot) &
the SIM card



Audio
Single speaker, 1.2w



Battery
3.7v/6450mAh,
supports fast charging



Dimensions
T1:
287.3*180.9*18.7 mm
Bracket:
239.5*219.5*195.6 mm



Weight
T1: 1006g
Bracket: 1200g



Temperature
Storage temperature: -35°C to 70°C
Operating temperature: -10°C to 55°C
Humidity: ≤95%



Dock Stand
Fingerprint: Optional
RJ45: Supports RJ45, WLAN ethernet
USB: 3*Type A USB ports
Wire Charger: DC interface, 9V/2A
Standing Charger: Magnetic suction connection charging

Certifications

